

Shell Kit for Pumpfix F, without nozzles, bl.cover

Article information

Item no.: 24000S-RBK GTIN: 4026092097069 Price group: 30

Description

KESSEL shell kit for Pumpfix F, without sockets, black cover

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating a Pumpfix F backwater pumping station.

General characteristics	
Colour:	black
Type of wastewater:	with sewage
Installation situation:	floor slab installation
Delivery state:	Pre-mounted for final assembly on site (pumps and
	sensor system must be fitted on site and control
	unit must be connected)
Inlet max. scoring (DN):	Z-53.2-388
Motor type:	KSM 140
Protection class (pump):	IP 68 (3m/48h)
Dimensions	15.0 km
Net weight:	15,2 kg
Gross weight:	18 kg
Groundwater resistant from lower edge of base	3000 mm
section:	750
Cutout dimension, width:	750 mm
Cutout dimension, length:	750 mm
Vertical drop between inlet and outlet:	9 mm
Installation depth:	516 - 669 mm
Vertical adjustment:	vertically adjustable upper section
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
System:	optional
-,	
Coverage features	
Type of cover:	Cover plate with slotted cover
	•



Cover material: Colour of cover: Width of cover: Length of cover: Drainage function: Cover locking: Load class: Odour trap: Polymer black 366 mm 366 mm yes Lock & Lift L 15 (EN 1253-1) Multistop