

Drain body The Universal DN 100, 3 inlets, w. backwater valve



Article information

Item no.: 27600

GTIN: 4026092085141

Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

PΡ

Variant

Waterproof flange: Pre-assembled at the factory

Waterproofing layer on the drain body: Connection flange

Sealing water height: 60 mm Mechanical backwater flaps: 2

General characteristics

Colour: black
Standard: EN 1253
Nominal size (DN): 100
Outer diameter (OD): 110 mm

Type of wastewater: without sewage Installation situation: floor slab installation Delivery state: installation-ready

Backwater protection: Type 5

Dimensions

Net weight: 2,31 kg Gross weight: 2,31 kg

Vertical adjustment: vertically adjustable upper section

Length: 380 mm Width: 285 mm Height: 190 mm



Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Material of drain body: PP System: lateral

Coverage features

Odour trap: included