


Submersible pump Aquadive GTF1000 resistant, with float switch, 10 m



Article information

Item no.: 28860C
GTIN: 4026092093771
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Submersible pump for faecal-free wastewater

Variant

Resistant:

Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems

Rim width:

Float switch

General characteristics

Type of wastewater:

without sewage

Dimensions

Net weight:

10 kg

Gross weight:

10,5 kg

Length:

195 mm

Width:

195 mm

Height:

290 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Wastewater contents

Pressure pipe connection: R 1 ¼ "

Pumping device

Pump control: GTF 1000 resistant

Weight: 10 kg

Connection type: coded plug

Rated current: 5,6 A

Length of mains cable for pump: 10 m

Self-diagnosis system (SDS): I

Insulation class: F

Protection class control unit: IP 68 (3m)

Max. temperature (permanent) of conveyed material: 40 °C

Hot water resistance for a short time (2 min): 80 °C

Max. pumping height: 10 m

Speed: 2700 U/min

Power P1: 1,3 kW

Power P2: 0,75 kW

Operating mode: S3 - 50 %

Type of fuse required (electrical protection): C 16 A

Type of pump connection cable: H07RN-F 3G 1.5 mm²

Impeller type: Multi-vane impeller

Free passage: 10 mm

Control

Type of level measurement: mechanical

Mains frequency: 50 Hz

Operating voltage: 230 V

Connection type: coded plug

Rated current: 5,6 A