


The Ultraflat 79 floor drain DN 50, Variofix, Des grating, L&L





Article information

Item no.: 44700.53 GTIN: 4026092080948

Price group: 10

Advantages

- Low installation depth
- Scientifically confirmed sound insulation effect
- different design covers

Description

The Ultraflat 79 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant

System: 125 SonicControl: optional

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water supply: W3-I
Sealing water height: 50 mm
Discharge rate (l/s) with 10 mm backwater: 1,2
Discharge rate (l/s) with 20 mm backwater: 1,4

General characteristics

Standard:EN 1253-1Nominal size (DN):50Outer diameter (OD):50 mm

Dimensions

Vertical adjustment: 119 - 174 mm
Net weight: 2,12 kg
Gross weight: 2,12 kg

Vertical adjustment: vertically adjustable upper section

Length: 312 mm Width: 312 mm



Height: 79 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS
System: lateral

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 120 mm
Height of cover: 16 mm
Length of cover: 120 mm
Surface: ground

Frame material: Stainless steel 14301

Cover locking: Lock & Lift Load class: L 15 (EN 1253-1)

Grating colour: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim length:132 mmRim material:132 mmShape of upper section:squareUpper section material:ABSOdour trap:included