



## Shower channel Linearis Compact L: 550 mm, DN 50, WaD, 304 SST cov., K 3



### Article information

Item no.: 45600.61M  
GTIN: 4026092078891  
Price group: 10

### Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

### Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

|                                            |                                                            |
|--------------------------------------------|------------------------------------------------------------|
| Variant                                    |                                                            |
| System:                                    | 125                                                        |
| SonicControl:                              | prepared                                                   |
| Waterproofing layer on the upper section:  | Factory-fitted sealing collar (WaD) according to DIN 18534 |
| Water supply:                              | W3-I                                                       |
| Sealing water height:                      | 22 mm                                                      |
| Discharge rate (l/s) with 10 mm backwater: | 0,6                                                        |
| Discharge rate (l/s) with 20 mm backwater: | 0,7                                                        |
| Discharge rate (l/s) without backwater:    | 0,5 mm                                                     |
| General characteristics                    |                                                            |
| Nominal size (DN):                         | 50                                                         |
| Outer diameter (OD):                       | 50 mm                                                      |
| Dimensions                                 |                                                            |
| Net weight:                                | 1,52 kg                                                    |
| Gross weight:                              | 2,08 kg                                                    |

|                          |                       |
|--------------------------|-----------------------|
| Outer dimension, length: | 615 mm                |
| Installation depth:      | 80 - 140 mm           |
| Width:                   | 191 mm                |
| Height:                  | 80 mm                 |
| Packaging dimension:     | length                |
| Packaging dimension:     | width                 |
| Packaging dimension:     | height                |
|                          |                       |
| Tank/drain body          |                       |
| Number of outlets:       | 1                     |
| Material of drain body:  | ABS                   |
|                          |                       |
| Coverage features        |                       |
| Type of cover:           | Stainless steel cover |
| Cover material:          | Stainless steel 14301 |
| Colour of cover:         | silver                |
| Surface:                 | Brushed SST           |
| Frame material:          | Stainless steel 14301 |
| Cover locking:           | placed                |
| Load class:              | K 3 (EN 1253-1)       |
| Grating colour:          | optionally tileable   |
| Rim length:              | 66 mm                 |
| Rim material:            | 550 mm                |
| Max. flooring height:    | 15 mm                 |
| Shape of upper section:  | square                |
| Upper section material:  | ABS                   |
| Odour trap:              | included              |