

Grease separat. EasyClean Modular free, NS 2, round, Direct disposal

Article information

Item no.: 93002.00/D1-R GTIN: Price group: 60

Advantages

- Ideal where access is tight
- can be divided into 3 parts for insertion, for an insertion opening of max. 66 cm
- Direct disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

Variant Sound absorption mat: Disposal variant: Nominal size (NS): Disposal system: Type of disposal:	two-piece chamber Direct 2 Disposal connection manual
General characteristics	
Material:	PE
Standard:	EN 1825
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection
Dimensione	Connection
Dimensions Not weight:	57 kg
Net weight: Gross weight:	68 kg
Set-up area, height:	1395 mm
Required access area, length:	1100 mm
Required access area, width:	1020 mm
Required access area, height:	690 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body



Outlet nominal size (DN): Inlet nominal size (DN):

Coverage features Type of cover: Cover locking: Tightness:

Wastewater contents Separator contents: Hose: 100 mm 100 mm

Cover Quick-release closure odour-tight

400 l 200 l