

## Technology kit Aqualift S Comp GTF1200Res Mon fl.switch



### Article information

Item no.: 281200C-TK  
GTIN: 4026092108130  
Price group: 20

### Description

For combination with a KESSEL shell kit for creating a Mono lifting station for wastewater without sewage with a GTF1200 wastewater pump. The ready to plug in lifting station for wastewater without sewage is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an open pump tank. One-handed closures enable easy removal of the integrated components. The system for installation in the floor slab is pre-assembled for final installation on site. KESSEL technology kit consisting of:

- Pump with multi-vane vortex impeller for maximum operating safety - Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems - Includes float switch for level measurement

#### Variant

Type of system:  
Resistant:

Single unit  
Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems  
Float switch

Rim width:

#### Dimensions

Net weight:  
Gross weight:  
Packaging dimension:  
Packaging dimension:  
Packaging dimension:

9,75 kg  
10,54 kg  
length  
width  
height

Tank/drain body  
Pumping volume:

16 l

Pumping device  
Pump control:

GTF 1200 resistant

Number of pumps:	1
Weight:	10 kg
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	6,2 A
Length of mains cable for pump:	5 m
Self-diagnosis system (SDS):	I
Insulation class:	F
Protection class control unit:	IP 68 (3m)
DSC:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping capacity:	15,5 m³/h
Max. pumping height:	9 m
Speed:	2650 U/min
Power P1:	1,4 kW
Power P2:	0,84 kW
Operating mode:	S3 - 10 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm²
Impeller type:	Multi-vane impeller
Free passage:	30 mm
Control	
Level measurement instrument:	Float switch
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	6,2 A